



CLEAN OIL  
BRIGHT IDEAS

# F 38/20

## CJC™ Offline Filter Insert

### CJC™ Product Sheet

#### APPLICATION

The CJC™ F 38/20 Filter Insert is ideal for the fine filtration of mineral and synthetic based

- quenching oil

#### FEATURES

- large surface area
- large dirt holding capacity
- fine filtration capability

#### FILTRATION CAPABILITY

##### • Particle Removal

All CJC™ Filter Inserts have the following filtration degree:

- **3 µm absolute:**  
98.7% of all solid particles > 3 µm
- **0.8 µm nominal:**  
50% of all solid particles > 0.8 µm

are retained in each pass.

The dirt holding capacity of an F 38/20 Insert is **3.5 litres** of evenly distributed solids.

##### • Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 4.5 kg** of degradation products.

##### • Water Removal

The water absorption potential is up to **50%** of the total contaminant holding capacity.

#### COMPONENT

CJC™ Filter Inserts type F consist of bonded discs. Ingredient: Wood cellulose.

#### IDENTIFICATION

To order the F 38/20 Filter Insert, please use:

##### Article No:

- F 38/40: PA5600307
- F 38/60: PA5600308
- (F 38/100: F 38/40 + F 38/60)

