



CLEAN OIL
BRIGHT IDEAS

FB 15/12

CJC™ Offline Filter Insert

CJC™ Product Sheet

APPLICATION

The CJC™ FB 15/12 Filter Insert is used in CJC™ Filters ideal for filtration of mineral based fuels:

- diesel oils
- gas oils

FILTRATION CAPABILITY

• Particle Removal

All CJC™ Filter Inserts have the following filtration degree:

- **3 μm absolute:**
98.7% of all solid particles $> 3 \mu\text{m}$
- **0.8 μm nominal:**
50% of all solid particles $> 0.8 \mu\text{m}$

are retained in each pass.

The dirt holding capacity of an FB 15/12 Insert is **0,75 litres** of evenly distributed solids.

• Degradation Products

Oxidation by-products, resin / sludge, and varnish are retained by the cellulose material. The cellulose will retain **appr. 0,5 kg** of degradation products.

• Water Removal

The type FB 15/12 Filter Insert will not permanently hold water, as its free passage is integral to the water separation process.

DIMENSIONS

The figures below are nominal:

Diameter: 15 cm
Height: 12 cm

COMPONENT

CJC™ Filter Inserts type FB consist of bonded discs. Ingredient: Wood cellulose.

IDENTIFICATION

To order the FB 15/12 Filter Insert, please use:

Article No: PA5601339

